

Y-FILTERS

For more info visit our website www.tempoinc.com



Features:

- Compact design.
- Available with 3/4" and 1" connections.
- Can be used at pressures up to 75 psi.
- Body is manufactured from high impact polypropylene.
- Polyester or stainless steel filtration screens available.
- Can be manually flushed by removing cap or opening ball valve.
- Connections are MIPT or hose thread swivel configuration.
- Made in USA.

Part No.	Flush Port	Inlet	Outlet	Screen	Max Pressure	Max Flowrate
FYF75	Cap	3/4" MIPT	3/4" MIPT	150 Mesh Polyester	75 psi	10 gpm
FYFS75	Cap	3/4" MIPT	3/4" MIPT	150 Mesh Stainless Steel	75 psi	10 gpm
FYF100	Cap	1" MIPT	1" MIPT	150 Mesh Polyester	75 psi	10 gpm
FYFS100	Cap	1" MIPT	1" MIPT	150 Mesh Stainless Steel	75 psi	10 gpm
FYF75V	Ball valve	3/4" MIPT	3/4" MIPT	150 Mesh Polyester	75 psi	10 gpm
FYFS75V	Ball valve	3/4" MIPT	3/4" MIPT	150 Mesh Stainless Steel	75 psi	10 gpm
FYF100V	Ball valve	1" MIPT	1" MIPT	150 Mesh Polyester	75 psi	10 gpm
FYFS100V	Ball valve	1" MIPT	1" MIPT	150 Mesh Stainless Steel	75 psi	10 gpm
FYFH75	Cap	3/4" FHT Swivel	3/4" MHT	150 Mesh Polyester	75 psi	10 gpm