

1/4" COBRA™ DRIPPERLINE

For more info visit our website www.tempoinc.com

Features:



- Emitters pre-inserted into 1/4" tubing at constant spacing.
- Standard 1/4" tubing (0.170" ID x 0.250" OD).
- Fits all 1/4" barbed fittings.
- Available in brown or black.
- 1/2 gph discharge rate per emitter.
- Turbulent flow emitter with built-in filtration.
- Operating pressure from 15 to 30 psi.
- Double outlet holes 180° apart.
- Very uniform discharge rates.
- Available in various coil lengths and dripper spacings.
- Easy to install.
- Made in USA.

Part No.	Discharge Rate	Spacing	Coil Length	Color	Tubing Size	Max length of run	Max pressure
ED12BL/1000	1/2 gph	12"	1,000'	Black	0.170" ID x 0.250" OD	32'	30 psi
ED6BL/1000	1/2 gph	6"	1,000'	Black	0.170" ID x 0.250" OD	18'	30 psi
ED12BL/500	1/2 gph	12"	500'	Black	0.170" ID x 0.250" OD	32'	30 psi
ED6BL/500	1/2 gph	6"	500'	Black	0.170" ID x 0.250" OD	18'	30 psi
ED12BL/100	1/2 gph	12"	100'	Black	0.170" ID x 0.250" OD	32'	30 psi
ED9BL/100	1/2 gph	9"	100'	Black	0.170" ID x 0.250" OD	25'	30 psi
ED6BL/100	1/2 gph	6"	100'	Black	0.170" ID x 0.250" OD	18'	30 psi
ED12BR/100	1/2 gph	12"	100'	Brown	0.170" ID x 0.250" OD	32'	30 psi
ED6BR/100	1/2 gph	6"	100'	Brown	0.170" ID x 0.250" OD	18'	30 psi
ED12BL/50	1/2 gph	12"	50'	Black	0.170" ID x 0.250" OD	32'	30 psi
ED6BL/50	1/2 gph	6"	50'	Black	0.170" ID x 0.250" OD	18'	30 psi
ED6BR/50	1/2 gph	6"	50'	Brown	0.170" ID x 0.250" OD	18'	30 psi

Discharge Rates (gph)

15 psi	20 psi	30 psi
0.45 gph	0.50 gph	0.60 gph